

Module 5: Classification

Linear Methods: Logistic Regression

STAT/BIOSTAT 527, University of Washington

Emily Fox

May 22nd, 2014

©Emily Fox 2014

1

Very convenient!

$$p(y = 0 | x, \beta) = \frac{1}{1 + \exp(\beta_0 + \sum_j \beta_j x_j)}$$

implies

$$p(y = 1 | x, \beta) = \frac{\exp(\beta_0 + \sum_j \beta_j x_j)}{1 + \exp(\beta_0 + \sum_j \beta_j x_j)}$$

1 - P(y=0|x)

Examine ratio:

$$\frac{p(y = 1 | x, \beta)}{p(y = 0 | x, \beta)} = \exp(\beta_0 + \sum_j \beta_j x_j) > 1 \Rightarrow \text{class 1 wins, else class 0 (under 0-1 loss)}$$

implies *log odds*

$$\log \frac{p(y = 1 | x, \beta)}{p(y = 0 | x, \beta)} = \beta_0 + \sum_j \beta_j x_j > 0 \Rightarrow \text{class 1 wins, as before}$$

linear

linear classification rule!

©Emily Fox 2014

2

Maximizing Conditional Log Likelihood

$$p(y=0 | x, \beta) = \frac{1}{1 + \exp(\beta_0 + \sum_j \beta_j x_j)}$$

$$p(y=1 | x, \beta) = \frac{\exp(\beta_0 + \sum_j \beta_j x_j)}{1 + \exp(\beta_0 + \sum_j \beta_j x_j)}$$

$$l(\beta) = \sum_i \log p(y_i | x_i, \beta)$$

$$= \sum_i y_i (\beta_0 + \sum_j \beta_j x_{ij}) - \log(1 + \exp(\beta_0 + \sum_j \beta_j x_{ij}))$$

$x \in \mathbb{R}^d$

fixed in training data

Good news: $l(\beta)$ is concave function of β , no local optima problems

Bad news: no closed-form solution to maximize $l(\beta)$


Good news: concave functions easy to optimize

©Emily Fox 2014

3

Optimizing Concave Function – Gradient Ascent

- Conditional likelihood for logistic regression is concave
- Find optimum with gradient ascent



Gradient: $\nabla_{\beta} l(\beta) = \left[\frac{\partial l(\beta)}{\partial \beta_0}, \dots, \frac{\partial l(\beta)}{\partial \beta_d} \right]'$

Step size, $\eta > 0$

Update rule: $\Delta \beta = \eta \nabla_{\beta} l(\beta)$

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \frac{\partial l(\beta)}{\partial \beta_j}$$

- Gradient ascent is simplest of optimization approaches

- e.g., Conjugate gradient ascent can be much better

Often, esp. proofs, η gets smaller w/ iterations
e.g. $\eta_t = \frac{1}{t}$ const.

©Emily Fox 2014

4

Gradient Ascent for LR

start w/ $\beta^{(0)}$ (e.g. 0)

revisit soon

Gradient ascent algorithm: iterate until change $< \epsilon$

$$\beta_0^{(t+1)} \leftarrow \beta_0^{(t)} + \eta \sum_i \left(y_i - \hat{p}(y = 1 \mid x_i, \beta^{(t)}) \right)$$

For $j=1, \dots, d$,

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \sum_i \underline{x_{ij}} \left(y_i - \hat{p}(y = 1 \mid x_i, \beta^{(t)}) \right)$$

repeat


©Emily Fox 2014

5


Regularization in Linear Regression

- Overfitting usually leads to very large parameter choices, e.g.:

$$-2.2 + 3.1 X - 0.30 X^2$$



$$-1.1 + 4,700,910.7 X - 8,585,638.4 X^2 + \dots$$



even for
 $n \gg p$,
 p large

- Regularized** or **penalized** regression aims to impose a “complexity” penalty by penalizing large weights


- “Shrinkage” method

$$\hat{\beta} = \arg \min_{\beta} \sum_{i=1}^n (y_i - (\beta_0 + \beta^T x_i))^2 + \lambda \|\beta\|$$

©Emily Fox 2014

6


Linear Separability



©Emily Fox 2014

7

Large Parameters → Overfitting



- If data is linearly separable, weights go to infinity

□ In general, leads to overfitting:

- Penalizing high weights can prevent overfitting...

©Emily Fox 2014

8

Regularized Conditional Log Likelihood

- Add regularization penalty, e.g., L_2 :

$$l(\beta) = \log \prod_{i=1}^n p(y_i | x_i, \beta) - \frac{\lambda}{2} \|\beta\|_2^2$$

- Practical note about β_0 :
- Gradient of regularized likelihood:

©Emily Fox 2014

9

Standard v. Regularized Updates

- Maximum conditional likelihood estimate

$$\hat{\beta} = \arg \max_{\beta} \log \prod_{i=1}^n p(y_i | x_i, \beta)$$

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \sum_i x_{ij} \left(y_i - \hat{p}(y = 1 | x_i, \beta^{(t)}) \right)$$

- Regularized maximum conditional likelihood estimate

$$\hat{\beta} = \arg \max_{\beta} \log \prod_{i=1}^n p(y_i | x_i, \beta) - \frac{\lambda}{2} \sum_{j=1}^d \beta_j^2$$

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \left\{ -\lambda \beta_j^{(t)} + \sum_i x_{ij} \left(y_i - \hat{p}(y = 1 | x_i, \beta^{(t)}) \right) \right\}$$

©Emily Fox 2014

10

Stopping Criterion

$$l(\beta) = \log \prod_{i=1}^n p(y_i | x_i, \beta) - \frac{\lambda}{2} \|\beta\|_2^2$$

- When do we stop doing gradient ascent?

- Because $l(\mathbf{w})$ is strongly concave:

- i.e., because of some technical condition

$$l(\beta^*) - l(\beta) \leq \frac{1}{2\lambda} \|\nabla l(\beta)\|_2^2$$

- Thus, stop when:

©Emily Fox 2014

11

Digression:

Logistic Regression for $K > 2$

- Logistic regression in more general case (K classes), where Y in $\{1, \dots, K\}$

©Emily Fox 2014

12

Digression:

Logistic Regression for $K > 2$

- Logistic regression in more general case, where $Y \text{ in } \{1, \dots, K\}$

for $k < K$

$$p(y = k | \mathbf{x}, \beta) = \frac{\exp(\beta_{k0} + \sum_{j=1}^d \beta_{kj} x_j)}{1 + \sum_{k'=1}^{K-1} \exp(\beta_{k'0} + \sum_{j=1}^d \beta_{k'j} x_j)}$$

for $k=K$ (normalization, so no weights for this class)

$$p(y = K | \mathbf{x}, \beta) = \frac{1}{1 + \sum_{k'=1}^{K-1} \exp(\beta_{k'0} + \sum_{j=1}^d \beta_{k'j} x_j)}$$

**Estimation procedure is basically the same
as what we derived!**

©Emily Fox 2014

13

The Cost, The Cost!!! Think about the cost...

- What's the cost of a gradient update step for LR???

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \left\{ -\lambda \beta_j^{(t)} + \sum_i x_{ij} (y_i - \hat{p}(y = 1 | x_i, \beta^{(t)})) \right\}$$

©Emily Fox 2014

14

Gradient ascent in Terms of Expectations

- “True” objective function:

$$l(\beta) = E_x[l(\beta, x)] = \int p(x)l(\beta, x)dx$$

- Taking the gradient:
- “True” gradient ascent rule:
- How do we estimate expected gradient?

©Emily Fox 2014

15

SGD: Stochastic Gradient Ascent (or Descent)

- “True” gradient: $\nabla l(\beta) = E_x[\nabla l(\beta, x)]$
- Sample based approximation:
- What if we estimate gradient with just one sample???
 - ☐ Unbiased estimate of gradient
 - ☐ Very noisy!
 - ☐ Called stochastic gradient ascent (or descent)
 - Among many other names
 - ☐ VERY useful in practice!!!

©Emily Fox 2014

16

Stochastic Gradient Ascent for Logistic Regression

- Logistic loss as a stochastic function:

$$E_x[l(\beta, x)] = E_x \left[\log p(y | x, \beta) - \frac{\lambda}{2} \|\beta\|_2^2 \right]$$

- Batch gradient ascent updates:

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \left\{ -\lambda \beta_j^{(t)} + \frac{1}{n} \sum_{i=1}^n x_{ij} \left(y_i - \hat{p}(y = 1 | x_i, \beta^{(t)}) \right) \right\}$$

- Stochastic gradient ascent updates:

- Online setting:

$$\beta_j^{(t+1)} \leftarrow \beta_j^{(t)} + \eta \left\{ -\lambda \beta_j^{(t)} + x_{i(t),j} \left(y_{i(t)} - \hat{p}(y = 1 | x_{i(t)}, \beta^{(t)}) \right) \right\}$$

©Emily Fox 2014

17

What you should know...

- Classification: predict discrete classes rather than real values
- Logistic regression model: Linear model
 - Logistic function maps real values to [0,1]
- Optimize conditional likelihood
- Gradient computation
- Overfitting
- Regularization
- Regularized optimization
- Cost of gradient step is high, use stochastic gradient descent

©Emily Fox 2014

18

Module 5: Classification

Linear Methods: LDA and QDA

STAT/BIOSTAT 527, University of Washington

Emily Fox

May 22nd, 2014

©Emily Fox 2014

19

Discriminative vs. Generative

- So far, we have considered modeling/fitting

$$p(Y \mid X)$$

- There are also a large set of **generative** methods

- Model:

- Class-conditional densities $f_k(X) =$
- Class prior probabilities π_k

- Via Bayes' rule:

©Emily Fox 2014

20

Generative Classifiers

$$p(Y = k \mid X = x) = \frac{\pi_k f_k(x)}{\sum_{\ell} \pi_{\ell} f_{\ell}(x)}$$

- Examples include:

- Linear and quadratic discriminative analysis (LDA and QDA)
- Mixture of Gaussians (saw in BNP module)
- Nonparametric density estimation for $f_k(x)$
- Naïve Bayes

©Emily Fox 2014

21

Linear Discriminative Analysis

- Assume Gaussian class-conditional densities

$$f_k(X) =$$

- Furthermore, consider equal covariances

- Log odds

$$\log \frac{p(Y = k \mid X = x)}{p(Y = \ell \mid X = x)} =$$

©Emily Fox 2014

22

Linear Discriminative Analysis

$$\log \frac{p(Y = k | X = x)}{p(Y = \ell | X = x)} = \log \frac{\pi_k}{\pi_\ell} - \frac{1}{2}(\mu_k + \mu_\ell)^T \Sigma^{-1}(\mu_k - \mu_\ell) + x^T \Sigma^{-1}(\mu_k - \mu_\ell)$$

- Equivalently,


$$\log \frac{p(Y = k | X = x)}{p(Y = \ell | X = x)} = \delta_k(x) - \delta_\ell(x)$$

where

$$\delta_k(x) =$$

- Decision rule:

- Linear decision boundaries



From Hastie, Tibshirani, Friedman book


©Emily Fox 2014

23

LDA Parameter Estimation

$$\log \frac{p(Y = k | X = x)}{p(Y = \ell | X = x)} = \log \frac{\pi_k}{\pi_\ell} - \frac{1}{2}(\mu_k + \mu_\ell)^T \Sigma^{-1}(\mu_k - \mu_\ell) + x^T \Sigma^{-1}(\mu_k - \mu_\ell)$$

- Based on the training class labels, estimate parameters:




From Hastie, Tibshirani, Friedman book

©Emily Fox 2014

24

Quadratic Discriminative Analysis

- Same setup as LDA, but allow class-specific covariances
- Quadratic discriminant functions:
 $\delta_k(x) =$
- Quadratic decision boundaries



From Hastie, Tibshirani, Friedman book

©Emily Fox 2014

25

QDA Parameter Estimation

- Based on the training class labels, estimate parameters:
- Number of parameters:
- Can also consider shrinkage estimators

$$\hat{\Sigma}_k(\alpha) = \alpha \hat{\Sigma}_k + (1 - \alpha) \hat{\Sigma} \quad \hat{\Sigma}(\gamma) = \gamma \hat{\Sigma} + (1 - \gamma) \sigma^2 I$$

©Emily Fox 2014

26

Notes on QDA and LDA

- LDA + QDA tend to perform very well in practice
- It is not true that data are Gaussian or, furthermore, that covariances are equal (LDA)
- Performance is likely attributed to the fact that the data can only support simple decision boundaries
 - Also, estimates for Gaussian models are stable

©Emily Fox 2014

27

LDA vs. Logistic Regression

- Both have linear log odds:

$$\log \frac{p(Y = k | X = x)}{p(Y = K | X = x)} = \alpha_{k0} + \alpha_k^T x$$

$$\log \frac{p(Y = k | X = x)}{p(Y = K | X = x)} = \beta_{k0} + \beta_k^T x$$

- Difference is in how the coefficients are estimated

$$p(X, Y = k) =$$

©Emily Fox 2014

28

LDA vs. Logistic Regression

$$p(X, Y = k) = p(X)p(Y = k | X)$$

- Marginal likelihood term

- Logistic regression:

- LDA:

©Emily Fox 2014

29

LDA vs. Logistic Regression

- In LDA, the data inform the parameters more
 - If data are indeed Gaussian, then asymptotically maximizing just conditional likelihood requires 30% more data to perform as well
- Data far from boundary affect Σ in LDA, but are ignored by logistic regression
- Observations without class labels can be used in mixture model case, but not in logistic regression
- Marginal likelihood $p(X)$ acts as a regularizer
- Logistic regression tends to be more robust than LDA and can handle qualitative X variables, but performance is often similar.

©Emily Fox 2014

30

Module 5: Classification

Nonparametric Methods: KDE and Naïve Bayes

STAT/BIOSTAT 527, University of Washington

Emily Fox

May 22nd, 2014


©Emily Fox 2014

31

KDE for Classification

$$p(Y = k \mid X = x) = \frac{\pi_k f_k(x)}{\sum_{\ell} \pi_{\ell} f_{\ell}(x)}$$

- Use KDE to estimate class-conditional densities
- Recall commonly used
Gaussian KDE in 1D




From Hastie, Tibshirani, Friedman book

©Emily Fox 2014

32

Example: Heart Disease Data

- Binary response = CHD (coronary heart disease)
- Predictor = systolic blood pressure




From Hastie, Tibshirani, Friedman book

©Emily Fox 2014

33

Example: Heart Disease Data

From Hastie, Tibshirani, Friedman book




- KDE estimates are poor in regions with little data
- Local linear model uses variable bandwidth based on k-NN
→ smooths out over these regions
- For classification tasks, do not need to estimate each class-conditional density well. Just need good estimates of the posterior near the decision boundary

©Emily Fox 2014

34

Class-Conditionals vs. Posterior



■ Example:

- Both densities are multimodal
- Might opt for rougher, high-variance estimator to capture features
- However, posterior is quite smooth
- Fine-scale features are irrelevant for classification here

©Emily Fox 2014

35

Multivariate KDE

■ In 1d

$$\hat{p}(x_0) = \frac{1}{n\lambda} \sum_{i=1}^n K_{\lambda}(x_0, x_i)$$

- In $\mathbb{R}^d$, assuming a product kernel,

$$\hat{p}(x_0) = \frac{1}{n\lambda_1 \cdots \lambda_d} \sum_{i=1}^n \left\{ \prod_{j=1}^d K_{\lambda_j}(x_{0j}, x_{ij}) \right\}$$

- lots of params to choose
- Typical choice = Gaussian RBF → Gaussian KDE

$$e^{-\frac{\|x_0 - x\|^2}{\lambda}}$$

©Emily Fox 2014

36

Naïve Bayes Classifier

$$p(Y = k \mid X = x) = \frac{\pi_k f_k(x)}{\sum_{\ell} \pi_{\ell} f_{\ell}(x)}$$

- Useful in high-dimensional settings (d large)
- Assumes factored form for class-conditional densities

$$f_k(X) =$$

- Benefits:
 - Estimate $f_{kj}(X_j)$ separately for each j using only 1D KDE
 - If X_j of X is discrete, then can combine using a histogram estimate

©Emily Fox 2014

37

Naïve Bayes Classifier

$$p(Y = k \mid X = x) = \frac{\pi_k \prod_j f_{kj}(x_j)}{\sum_{\ell} \pi_{\ell} \prod_j f_{\ell j}(x_j)}$$

- Log odds

$$\log \frac{p(Y = k \mid X = x)}{p(Y = \ell \mid X = x)} =$$

- Has form of GAM, but fit very differently
 - Analogous to difference between LDA and logistic regression

©Emily Fox 2014

38

Module 5: Classification

Mixture Models for Classification

STAT/BIOSTAT 527, University of Washington

Emily Fox

May 22nd, 2014


©Emily Fox 2014

39

Density as Mixture of Gaussians


- Approximate density with a mixture of Gaussians

Mixture of 3 Gaussians



$$p(x_i | \pi, \mu, \Sigma) = \sum_{k=1}^K \pi_k N(x_i | \mu_k, \Sigma_k)$$

K # of mix comp.
 π_k mix. weights
 μ_k, Σ_k shape params




Gauss. kernel, just like in KDE, but not centered at obs

©Emily Fox 2014

40

Clustering our Observations


- Imagine we have an assignment of each x_i to a Gaussian



C. Bishop, Pattern Recognition & Machine Learning

Clustering our Observations

- Imagine we have an assignment of each x_i to a Gaussian



- Introduce latent cluster indicator variable z_i

$$z_i \in \{1, \dots, K\}$$

$$Pr(z_i = k) = \pi_k$$

- Then we have

$$p(x_i | z_i, \pi, \mu, \Sigma) =$$


$$N(x_i | \mu_{z_i}, \Sigma_{z_i})$$

*param. est. is easy if we have $\{z_i\}$
 $\Rightarrow$ decoupled into K Gauss. est.*

C. Bishop, Pattern Recognition & Machine Learning

Clustering our Observations

- We must infer the cluster assignments from the observations



- Posterior probabilities of assignments to each cluster *given* model parameters:

$$r_{ik} = p(z_i = k \mid x_i, \pi, \theta) =$$

$$= \frac{\pi_k N(x_i \mid \mu_k, \Sigma_k)}{\sum_j \pi_j N(x_i \mid \mu_j, \Sigma_j)}$$

motivates an iterative alg.

C. Bishop, Pattern Recognition & Machine Learning

Mixture Models for Classification

- Can use mixture models as a generative classifier in the unsupervised setting

- EM algorithm = iteratively:

- Estimate responsibilities given parameter estimates


$$\hat{r}_{ik} = \frac{\hat{\pi}_k N(x_i, \hat{\mu}_k, \hat{\Sigma}_k)}{\sum_{\ell} \hat{\pi}_{\ell} N(x_i, \hat{\mu}_{\ell}, \hat{\Sigma}_{\ell})}$$

- Maximize parameters given responsibilities

- For classification, threshold the estimated responsibilities


- E.g., $\hat{g}(x_i) = \arg \max_k \hat{r}_{ik}$

- Note: allows non-linear boundaries as in QDA



Example: Heart Disease Data

- Binary response = CHD (coronary heart disease)
- Predictor = systolic blood pressure



From Hastie, Tibshirani, Friedman book

©Emily Fox 2014

45

What you need to know

- Discriminative vs. Generative classifiers
- LDA and QDA assume Gaussian class-conditional densities
 - Results in linear and quadratic decision boundaries, respectively
- KDE for classification
 - Challenging in areas with little data or in high dimensions
 - Estimating class-conditionals is not optimizing classification objective
- Naïve Bayes assumes factored form
 - Results in log odds that have GAM form
- Mixture models allow for unsupervised generative approach

©Emily Fox 2014

46

Readings



- Hastie, Tibshirani, Friedman – 4.3, 4.4.5, 6.6.2-6.6.3, 6.8